

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **AESUB Blue / 400ml**
Registration number (REACH) not relevant (mixture)

Other means of identification

article number 401592

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses coating
Uses advised against do not use for products which come into contact with foodstuffs
do not use for private purposes (household)

1.3 Details of the supplier of the safety data sheet

Scanningspray Vertiebs UG (haftungsbeschränkt)
Gersdorffstr. 20a
44225 Dortmund
Germany
e-mail: info@scanningspray.de
Website: www.scanningspray.de

Competent person responsible for the safety data sheet Max Ruhfus
e-mail (competent person) ruhfus@scanningspray.de

1.4 Emergency telephone number

Emergency information service 24 Stunden Notrufnummer: Vergiftungs-Informationen-Zentrale Freiburg +49 (0) 761 / 192 40
This number is only available during the following office hours: Mon-Fri 00:00 - 00:00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	Cat. 1	(Aerosol 1)	H222, H229
4.1C	hazardous to the aquatic environment - chronic hazard	Cat. 3	(Aquatic Chronic 3)	H412

Remarks

For full text of H-phrases: see SECTION 16.

Supplemental hazard information

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word

Danger

Pictograms

GHS02



Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.

Precautionary statements - storage

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant.

Additional labelling requirements

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

There is no additional information.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	wt%	Classification acc. to 1272/2008/EC	Pictograms
cyclopentane	CAS No 287-92-3 EC No 206-016-6 REACH Reg. No 01-2119463053-47	25 - < 50	Flam. Liq. 2 / H225 Aquatic Chronic 3 / H412	

Safety Data Sheet








according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

Name of substance	Identifier	wt%	Classification acc. to 1272/2008/EC	Pictograms
propane	CAS No 74-98-6 EC No 200-827-9 REACH Reg. No 01-2119486944-21- xxxx	25 - < 50	Flam. Gas 1 / H220 Press. Gas L / H280	
ethanol	CAS No 64-17-5 EC No 200-578-6 REACH Reg. No 01-2119457610-43- xxxx	10 - < 25	Flam. Liq. 2 / H225	
Tricyclo[3.3.1.1.3,7]decane	CAS No 281-23-2 EC No 206-001-4 REACH Reg. No 01-2120041464-63- xxxx	5 - < 10	Aquatic Acute 1 / H400	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	EC No 926-605-8 REACH Reg. No 01-2119486291-36- xxxx	1 - < 5	Flam. Liq. 2 / H225 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC No 921-024-6 REACH Reg. No 01-2119475514-35- xxxx	1 - < 5	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	EC No 931-254-9 REACH Reg. No 01-2119484651-34- xxxx	1 - < 5	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	EC No 927-510-4 REACH Reg. No 01-2119475515-33- xxxx	1 - < 5	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

Name of substance	Identifier	wt%	Classification acc. to 1272/2008/EC	Pictograms
n-hexane	CAS No 110-54-3 EC No 203-777-6 REACH Reg. No 01-2119480412-44- xxxx	< 1	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 Repr. 2 / H361 STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, BC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

nitrogen oxides (NO_x), carbon monoxide (CO), carbon dioxide (CO₂)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

• Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

• Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

• Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
EU	n-hexane	110-54-3	IOEL V	20	72						2006/15/EC
GB	hydrocarbon mixture (RCP method)		WEL		1,500		3,000				EH40/2005
GB	n-hexane	110-54-3	WEL	20	72						EH40/2005
GB	cycloalkanes, C5-C6	287-92-3	WEL		1,800						EH40/2005
GB	ethanol	64-17-5	WEL	1,000	1,920						EH40/2005

Notation

Ceiling-C
STEL

Ceiling value is a limit value above which exposure should not occur
Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs/DMELs/PNECs and other threshold levels

• relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
ethanol	64-17-5	DNEL	1,900 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
ethanol	64-17-5	DNEL	343 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
ethanol	64-17-5	DNEL	950 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		DNEL	13,964 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		DNEL	5,306 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		DNEL	773 mg/kg	human, dermal	worker (industry)	chronic - systemic effects

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		DNEL	2,035 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C6, isoalkanes, <5% n-hexane		DNEL	5,306 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C6, isoalkanes, <5% n-hexane		DNEL	13,964 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		DNEL	300 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		DNEL	2,085 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
n-hexane	110-54-3	DNEL	11 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
n-hexane	110-54-3	DNEL	75 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

• relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
ethanol	64-17-5	PNEC	580 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethanol	64-17-5	PNEC	2.75 mg/l	aquatic organisms	water	intermittent release

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Personal protective equipment shall be used when the risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Eye/face protection

Wear eye/face protection.

Skin protection

• hand protection

Wear suitable gloves. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	aerosol (spray aerosol)
Colour	various
Odour	characteristic

Other physical and chemical parameters

pH (value)	
Melting point/freezing point	not determined
Initial boiling point and boiling range	-161.5 °C at 1,013 hPa
Flash point	<-29 °C at 101.3 kPa
Evaporation rate	not determined
Flammability (solid, gas)	Flammable aerosol in accordance with GHS criteria
Explosive limits	
• lower explosion limit (LEL)	0.6 vol%
• upper explosion limit (UEL)	15 vol%
Vapour pressure	25 kPa at 20 °C
Density	not determined
Relative density	Information on this property is not available.
Solubility(ies)	not determined
Partition coefficient	
n-octanol/water (log KOW)	This information is not available.
Auto-ignition temperature	264 °C
Viscosity	not relevant (aerosol)
Explosive properties	none
Oxidising properties	none

9.2 Other information

Solvent content	67.36 %
Solid content	0 %
propellant content	32.64 %

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. - Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

Physical stresses which might result in a hazardous situation and have to be avoided

strong shocks

10.5 Incompatible materials

oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity (STOT)

Shall not be classified as a specific target organ toxicant.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
propane	74-98-6	LC50	27.98 mg/l	fish	96 h
propane	74-98-6	EC50	7.71 mg/l	algae	96 h
ethanol	64-17-5	LC50	14.2 g/l	fish	96 h
ethanol	64-17-5	EC50	12.9 g/l	fish	96 h
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		LL50	12 mg/l	fish	96 h
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		EL50	17.06 mg/l	aquatic invertebrates	48 h
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		LL50	15.8 mg/l	fish	72 h
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		EL50	3 mg/l	aquatic invertebrates	48 h
Hydrocarbons, C6, isoalkanes, <5% n-hexane		LL50	18.27 mg/l	fish	96 h
Hydrocarbons, C6, isoalkanes, <5% n-hexane		EL50	31.9 mg/l	aquatic invertebrates	48 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		LL50	>13.4 mg/l	fish	96 h
n-hexane	110-54-3	LL50	12.51 mg/l	fish	96 h
n-hexane	110-54-3	EL50	21.85 mg/l	aquatic invertebrates	48 h

Aquatic toxicity (chronic)

May cause long-term adverse effects in the aquatic environment.

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ethanol	64-17-5	LC50	>0.08 mg/l	fish	42 d
ethanol	64-17-5	EC50	22.6 g/l	algae	10 d
ethanol	64-17-5	ErC50	675 mg/l	algae	4 d
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		EL50	12 mg/l	aquatic invertebrates	24 h

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

12.2 Persistence and degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
ethanol	64-17-5	oxygen depletion	74 %	5 d
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		oxygen depletion	83 %	10 d
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		oxygen depletion	83 %	16 d
Hydrocarbons, C6, isoalkanes, <5% n-hexane		oxygen depletion	83 %	10 d

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
propane	74-98-6		1.09 (pH value: 7, 20 °C)	
ethanol	64-17-5		-0.35 (pH value: 7.4, 24 °C)	
Hydrocarbons, C6, isoalkanes, <5% n-hexane		501.2	3.6 (pH value: 7, 20 °C)	
n-hexane	110-54-3	501.2	4 (pH value: 7, 20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

SECTION 14: Transport information

14.1	UN number	1950
14.2	UN proper shipping name	AEROSOLS
14.3	Transport hazard class(es)	
	Class	2 (gases) (aerosol)
	Subsidiary risk(s)	2.1 (flammability)
14.4	Packing group	not assigned to a packing group
14.5	Environmental hazards	none (non-environmentally hazardous acc. to the dangerous goods regulations)
14.6	Special precautions for user	
	Provisions for dangerous goods (ADR) should be complied within the premises.	
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	
	The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	1950
Proper shipping name	AEROSOLS
Class	2
Classification code	5F
Danger label(s)	2.1



Special provisions (SP)	190, 327, 344, 625
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D

• International Maritime Dangerous Goods Code (IMDG)

UN number	1950
Proper shipping name	AEROSOLS
Class	2.1
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

EmS	F-D, S-U
Stowage category	-
• International Civil Aviation Organization (ICAO-IATA/DGR)	
UN number	1950
Proper shipping name	Aerosols, flammable
Class	2.1
Danger label(s)	2.1



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

- **Directive 75/324/EEC relating to aerosol dispensers**

Classification of the gas/aerosol Extremely flammable

Labelling

Pressurized container: may burst if heated
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Do not pierce or burn, even after use
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
IOELV	Indicative occupational exposure limit value
log KOW	n-Octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Press. Gas	Gas under pressure
RCP	Reciprocal calculation procedure
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Repr.	Reproductive toxicity
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



AESUB Blue / 400ml

Version number: GHS 2.1
Replaces version of: 2018-12-12 (GHS 1)

revision: 2019-02-06

Abbr.	Descriptions of used abbreviations
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurized container: may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Specific end use(s)

Coating

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.